



# ASRE<sup>®</sup> ENGINEERING

## Flow Measuring Devices


**Contact:** +91 99873 18525  
+91 72081 48600

**Emails:** asredevices@gmail.com  
asreengineering@gmail.com

**Website:** www.asreengineering.in


**Address:** 165/2, Near Star Garden Hall, Khardi Rd,  
Opp Bharat Gears Ltd, Mumbra - Thane  
400612 Maharashtra, India.

**Tubular Level Indicator**



Range : Up to 3000mm  
MOC : M.S / C.S / SS304 / SS304L /  
SS316 / SS316L / PP  
Pressure Rating : Up to 7 kg/cm<sup>2</sup> (For PP 2 kg/cm<sup>2</sup>)  
Temperature Rating : Up to 150 °C (For PP 100 °C)  
Connection : Flange End / Screwed End

**Float & Board Level Indicator**



Range : Up to 10m  
MOC : M.S / C.S / SS304 / SS304L /  
SS316 / SS316L  
Pressure Rating : Up to 1 kg/cm<sup>2</sup>  
Temperature Rating : Up to 150 °C  
Connection : Flange End / Screwed End

**Full View Sight Glass**



Size : 15 NB to 150 NB  
MOC : M.S / C.S / SS304 / SS304L /  
SS316 / SS316L / PTFE Lined  
Pressure Rating : Up to 10 Kg/cm<sup>2</sup>  
Temperature Rating : Up to 200°C  
Connection : Flange End

**Double Window Sight Glass**



Range : 15 NB to 400 NB  
MOC : CI / M.S / C.S / SS304 / SS304L /  
SS316 / SS316L / PTFE Lined  
Pressure Rating : Up to 40 kg/cm<sup>2</sup>  
Temperature Rating : Up to 200 °C  
Connection : Flange End

**Electromagnetic Flow Meter**



Range : 15 mm to 1000 mm  
Body Material : CS / SS 304 / SS 316  
Electrode : SS 316 / Hastelloy B / Hastelloy C  
Pressure Rating : 0.6 to 4.0 MPa  
Connection : Flange End / Tri-clamp / Thread